



LED STREET LIGHT LUMINAIRE DU2R1080-A2S-BRN-CW

70W-400W HPS Replacement

- Parking Lots • Area Lighting • Street Light • Highways

FEATURES

WARRANTY	5 Years
POWER SAVING	At least 60%
PRODUCT LIFE	>75,000 hrs @ 12 hrs/day for 10 years
HEAT DISSIPATION	Patented design for optimum efficiency
MODULAR DESIGN	Module can be replaced directly for alternate application
KNUCKLE	Adjustable from 0-degree to 90-degree
LAB TESTED	IES Standards Tested
SOLID STATE	High-shock, High-vibration resistant.
HIGH CRI	75 CRI enhances all original colors



©Decors USA LLC

Phone: 866.248.6300 | 732.486.8520 | www.decorsusa.com | sales@decorsusa.com



LED STREET LIGHT LUMINAIRE DU2R1056-A2S-BRN-CW

SPECIFICATIONS

COLOR	3000K & 5000K
TOTAL CONSUMPTION	240W
INPUT VOLTAGE	120-277VAC
WORKING CURRENT	700MA
POWER FACTOR	0.96
LED QUANTITY	80
TOTAL LUMENS	36,000 lm
EFFICACY	140 lm/w
LED	OSRAM/PHILLIPS
BEAM PATTERN	Type II (A2S)
POLE MOUNTING DIAM.	2.4 inches (60mm)
IP RATING	IP65 UL Listed DLC
FIXTURE DIMENSIONS	31.5" x 12.5" x 3.7"
PACKAGE DIMENSIONS	34" x 14.5" x 7"
WORKING CONDITIONS	Temperature: -40C - 55C 10% - 95% Humidity
GROSS WEIGHT	19.9 lbs
NET WEIGHT	17.2 lbs
PACKING	L770 x W440 x H200 mm
FIXTURE FINISHING	Brown Bronze

Site Lighting

- LED Parking Lot Light Fixture
- **Square Pole Adapter Included**

Parking Lot lighting is based on I-FC across the whole site at 30ft. Pole height can be adjusted to meet local codes. It is the responsibility of the architect to achieve I-FC across the whole site.

Pole to be provided by GC.

