



# LED STREET LIGHT LUMINAIRE

## DU2R1028-A2S-BRN-CW

### 70W-400W HPS Replacement

- Parking Lots • Area Lighting • Street Light • Highways

#### FEATURES

WARRANTY	5 Years
POWER SAVING	At least 60%
PRODUCT LIFE	>75,000 hrs @ 12 hrs/day for 10 years
HEAT DISSIPATION	Patented design for optimum efficiency
MODULAR DESIGN	Module can be replaced directly for alternate application
KNUCKLE	Adjustable from 0-degree to 90-degree
LAB TESTED	IES Standards Tested
SOLID STATE	High-shock, High-vibration resistant.
HIGH CRI	75 CRI enhances all original colors



©Decors USA LLC

Phone: 866.248.6300 | 732.486.8520 | [www.decorsusa.com](http://www.decorsusa.com) | [sales@decorsusa.com](mailto:sales@decorsusa.com)



## LED STREET LIGHT LUMINAIRE DU2R1028-A2S-BRN-CW

### SPECIFICATIONS

COLOR	3000K & 5000K
TOTAL CONSUMPTION	70W
INPUT VOLTAGE	120-277VAC
WORKING CURRENT	700MA
POWER FACTOR	0.96
LED QUANTITY	24
TOTAL LUMENS	9,800 lm
EFFICACY	140 lm/w
LED	OSRAM/PHILLIPS
BEAM PATTERN	Type II (A2S)
POLE MOUNTING DIAM.	2.4 inches (60mm)
IP RATING	IP65   UL Listed   DLC
FIXTURE DIMENSIONS	24" x 10" x 4"
PACKAGE DIMENSIONS	26" x 12" x 8"
WORKING CONDITIONS	Temperature: -40C - 55C   10% - 95% Humidity
GROSS WEIGHT	11.7 lbs
NET WEIGHT	9.5 lbs
PACKING	L770 x W440 x H200 mm
FIXTURE FINISHING	Brown Bronze

#### Site Lighting

- LED Parking Lot Light Fixture
- **Square Pole Adapter Included**

Parking Lot lighting is based on I-FC across the whole site at 30ft. Pole height can be adjusted to meet local codes. It is the responsibility of the architect to achieve I-FC across the whole site.

**Pole to be provided by GC.**

